
PART #


## SH48A

310.318.2491 • 800.523.1269 • www.mockett.com


NOTE:

- Weight capacity is 25 lbs.
- Shelf projection is 8" MAX.
- Bracket spacing is 24" MAX.
- Shelf thickness is 8.00mm (5/16") MIN. to 32.00mm (1-1/4") MAX.





**REAR VIEW** 




Top bracket Mounting screw Install the top bracket of the SH48A. Make sure


HK-Anchor

(for drywall use ONLY)

Determine the position and location of the part on the work surface. Mark the mounting positions for the mounting hardware.


3





Stick the (2) soft plastic inserts on the top front of the lower bracket and under the top front of the top bracket. (Note: Additional soft plastic inserts are provided but not required.)






Install the shelf to the SH48A by tightening the machine screw until the shelf is secure. (Note: DO NOT overtighten the machine screw.)

the part is leveled and aligned straight. Then, install the part with the mounting hardware.





Align the lower bracket to the top bracket. Secure the part with the machine screw.

TABLE OF CONTENTS:

	1X SH48A
ACCO.	2X HK-Anchor
$\Diamond$	4X Soft plastic insert
and	1X Machine screw
and the same of th	2X 1-7/8" No. 10 Wood screws
	2X Plastic anchor

(Not Required for Install)