



- NOTES:**
1. USB ports are for charging use ONLY.
 2. Minimum clearance required 18" under the worksurface.
 3. 1/2" MIN. to 2" MAX. table thickness.

FRONT VIEW REAR VIEW



P.O. BOX 3333
 MANHATTAN BEACH, CA 90266 USA
 PHONE: 310.318.2491 FAX: 310.376.7650
 email: info@mockett.com www.mockett.com

PROPRIETARY AND CONFIDENTIAL.
 ALL DIMENSIONS HAVE A +/- 1/32" TOLERANCE UNLESS OTHERWISE SPECIFIED. WE DO NOT RECOMMEND DRILLING OR CUTTING ANY HOLES BEFORE RECEIVING A PRODUCT OR A PRODUCT SAMPLE.
 ALL MEASUREMENTS ARE IN INCHES.

| | | | | | |
|---------------------------|--------------------------|---------------------|-----------------------------|---------------------|------------------|
| PART NAME: PCS64/2/USB | | DRAWN BY: FM | LAST EDITED: FM | REQUESTED BY: MG | SHEET: 1 OF 1 |
| SCALE: N.T.S. | TOLERANCE: ± 1 / 16 " | DATE: 2019.04.22 | DATE: 2019.08.01 12:00am | APPROVED BY: - | |